



KOREAN PATENT ABSTRACTS(KR)

Document Code:A

(11) Publication No.1020030072855

(43) Publication.Date. 20030919

(21) Application No.1020020012116

(22) Application Date. 20020307

(51) IPC Code:

H05K 3/40

(71) Applicant:

SIMM TECH CO., LTD.

(72) Inventor:

LEE, HUI YONG

LEE, U SEOP

PARK, JEONG GWON


SUNWOO, JEONG HO

(30) Priority:

(54) Title of Invention

METHOD FOR PLATING BUMP PAD OF PRINTED CIRCUIT BOARD FOR FLIP CHIP BGA SEMICONDUCTOR PACKAGE

Representative drawing



(57) Abstract:

PURPOSE: A method is provided to reduce plating defects by permitting the bump pad connected to the solder ball land through a via hole to be electroplated together with the solder ball land.

CONSTITUTION: A method comprises a first copper plating step of electroless copper plating the solder ball land of a substrate having a via hole; a first imaging step of attaching a dry film on the copper plate land, and exposing only the connection portion between the circuit and the solder ball land by exposing and developing the resultant structure; a second copper plating step of forming a lead wire for interconnecting the circuit and the solder ball land; a first strip step of removing the dry film; a first etching step of removing the copper foil from the portion which is not electroplated; a second imaging step of attaching a solder mask on the solder ball land, and exposing a certain part of the lead wire by exposing and developing the resultant structure; a plating resist

depositing step of depositing a plating resist on the exposed part of the lead wire; an electro nickel/gold plating step of nickel plating the solder ball lands connected to the lead wire and the bump pad connected to the solder ball land, and performing a gold plating process; a second strip step of removing the solder mask and plating resist; and a second etching step of removing the copper foil from the lead wire which is not nickel/gold-plated, by performing an alkali copper etching process.

© KIPO 2003

if display of image is failed, press (F5)